

Tunnel Light



Artemis Series Tunnel Light

- Aluminum alloy housing and electrostatic sprayed surface give good resistance to corrosion, complying with RoHS standard.
- Built-in chimney effect thermal management system could solve the decrease of heat dissipation ability caused by dirt retention.
- Modular structure could be applied for power variation by the increase or decrease of the modules.
- Glareless lighting with Patented light distribution technology, safe for driving.
- Fast plug-in-out connector ensures a much easier maintenance.



IP 66

Item No.	System Power (W)	Module Qty	Lumen Output 5000K (lm)	CCT	Driver Efficiency	Dimension(mm)
TL2R2801	33	1	3100	5000±300K	>91%	L221×W330×H267
TL2R2802	62	2	5800	5000±300K	>91%	L253×W330×H267
TL2R2803	93	3	8800	5000±300K	>91%	L315×W330×H267
TL2R2804	123	4	12300	5000±300K	>92%	L377×W330×H267
TL2R2805	155	5	15500	5000±300K	>92%	L439×W330×H267
TL2R2806	185	6	18500	5000±300K	>92%	L501×W330×H267
TL2R2807	216	7	21600	5000±300K	>92%	L563×W330×H267
TL2R2808	246	8	24600	5000±300K	>92%	L625×W330×H267
TL2R2809	277	9	27700	5000±300K	>92%	L687×W330×H267
TL2R2810	308	10	30800	5000±300K	>92%	L749×W330×H267

Ordering Information

TL2R **2808** **A2** **50** **MB** **V27** **2 0**
 1 2 3 4 5

1 System Power	2801: 33W 2802: 62W	2803: 93W 2804: 123W	2805: 155W 2806: 185W	2807: 216W 2808: 246W	2809: 277W 2808: 308W
2 Light Distribution	A2			S1	
3 Color Temp	30: 3000±300K		40: 4000±300K		50: 5000±300K
4 Housing Color	MB: Matt Black		SG: Silver Grey		
5 Input Voltage	A22: AC 220-240 V		V27: AC 120-277V		V48: AC 347-480V

