


## Artemis Series Wallpack Light



- Uniform luminance, glare-free, applicable for parking lot lighting.
- Aluminum alloy, high corrosion resistance and weather-resistance.
- Built-in chimney effect thermal management system with self-cleaning effect and reliable performance.
- Patented removable-modular design for power variation.




**IP 66** Life Time 50,000hrs Working Temp -35°C - 50°C Working Humidity < 95% Power Factor > 0.95

Item No.	System Power (W)	Module Q'ty	Lumen Output 5000K (lm)	CCT	Driver Efficiency	Dimension(mm)
FL2F28012	33	1	3100	5000±300K	>91%	L229×W445×H154
FL2F28022	62	2	5800	5000±300K	>91%	L253×W445×H154
FL2F28032	93	3	8800	5000±300K	>91%	L315×W445×H154
FL2F28042	123	4	12300	5000±300K	>92%	L377×W445×H154
FL2F28052	155	5	15500	5000±300K	>92%	L439×W445×H154
FL2F28062	185	6	18500	5000±300K	>92%	L501×W445×H154
FL2F28072	216	7	21600	5000±300K	>92%	L563×W445×H154
FL2F28082	246	8	24600	5000±300K	>92%	L625×W445×H154
FL2F28092	277	9	27700	5000±300K	>92%	L687×W445×H154
FL2F28102	308	10	30800	5000±300K	>92%	L749×W445×H154

Ordering Information	FL2F 2806 S1 50 DG V27 2 0				
	1	2	3	4	5
1 System Power	2801: 33W 2802: 62W	2803: 93W 2804: 123W	2805: 155W 2806: 185W	2807: 216W 2808: 246W	2809: 277W 2810: 308W
2 Light Distribution	A2			S1	
3 Color Temp	30: 3000±300K		40: 4000±300K		50: 5000±300K
4 Housing Color	MB: Matt Black		DG: Dark Grey		WH: White
5 Input Voltage	A22: AC 220-240V		V27: AC 120-277V		V48: AC 347-480V




Light Distribution Curve



Luminous Intensity Unit : cd/klm  
Lens Code : S1S113  
Type I

Light Distribution Curve



Luminous Intensity Unit : cd/klm  
Lens Code : A2S111  
Type II